

# SPECIFICATII TEHNICE

## LAMPA SOLARA LED WESTECH

Lampa solara cu LED are un design modern si se foloseste exclusiv de energia solara fara a fi necesara conectarea ei la o sursa de energie electrica.

Avand o carcasa impermeabila si utilizand doar energia solara este rezistenta si la ploaie asa ca poate fi montata si in gradini, pe pereti exteriori, parcuri sau curti, fiind rezistenta chiar si la conditiile de clima severe datorita clasei de protectie Ip65.

Model	SL012-60W	SL012-120W	SL012-180W	SL012-240W
Panou solar	6V/20W	6V/30W	6V/50W	6V/75W
	Silicon Policristalin	Silicon Policristalin	Silicon Policristalin	Silicon Policristalin
Baterie	3. 2V/20AH	3. 2V/30AH	3.2V/45AH	3.2V/60AH
	LiFePO4	LiFePO4	LiFePO4	LiFePO4
Marca cip	Epistar	Epistar	Epistar	Epistar
Model cip(marime)	SMD 5050	SMD 5050	SMD 5050	SMD 5050
Lumeni	1500 LM	2370 LM	2746 LM	3570 LM
Mod control	Senzor crepuscul + Telecomanda + Senzor miscare(radar)			
CCT / IRC	6500~7500K / Ra $\geq$ 75			
Unghi iluminare	150*70°			
Timp de lucru	10-12 Ore			
Timp incarcare	5-6 Ore (In lumina directa a soarelui)			
Temp. lucru	-20°C ÷ 60°C			
Grad protectie	IP65			
Inaltime Instalare	3-4m	4-5m	5-6m	6-7m
Dimensiuni panou solar(mm)	445*345	595*345	895*345	1095*345
Dimensiuni produs (mm)	450*350*130	600*350*130	900*350*130	1100*350*130

