

# SURSA NEINTRERUPTIBILA DE TENSIUNE EAP ULTIMATE seria ST

Model.		EAP ST 500VA	EAP ST 800VA	EAP ST 1000VA	EAP ST 1500VA	EAP ST 2000VA
Putere nominala		300W	480W	600W	900W	1200W
Transformator		El / Toroidal		Toroidal		
Tensiune baterie		12VDC			24VDC	
Mod CA	Tensiune nominala intrare	230V				
	Interval tensiune nominala	155-285V				
	Frecventa intrare	45-65Hz				
	Tensiune iesire AVR	-10%, +8% (207-248V)				
	Transfer subtensiune	Comutati in Modul Inverter cand tensiune de intrare este <145V, Reveniti la Modul CA cand tensiunea de intrare este >155V				
	Transfe Supratensiune	Comutati in Modul Inverter cand tensiune de intrare este <285V, Reveniti la Modul CA cand tensiunea de intrare este >275V				
Mod Inverter	Tensiune nominala iesire	230V				
	Frecventa iesire	50Hz ± 0.1Hz				
	Forma undei la iesire	Sinusoidala pura				
	Eficienta	max 75%				
Curent maxim incarcare		8A	10A	15A	15A	15A
Timp transfer		<10ms				
Protectii		Supraincercare, scurt circuit, supraincalzire, over charge, supradescarcare, conectare inversa a bateriei				
Display		Tensiune CA intrare, Tensiune CA iesire, Frecventa iesire, Incarcare baterie/capacitate baterie, Capacitate incarcare, Mod CA, Mod inverter, Supraincercare, Eroare				
Alarma sonora		Da				
Alte caracteristici		Selector incarcare curent 3 nivele (30%-60%-100%)				
		Cablul bateriei 0.8m (+,-) fixat in UPS				
		cleme baterie - 1 pereche				
Intrare		Cablul 1.35m cu stecher shuko				
Iesire		1 x	2 x			
Conditii functionare	Nivel IP	IP20				
	Temperatura functionare	-5°C ~ +45°C				
	Umiditate functionare	<90%, fara condens				
	Nivel zgomot	<50dB la distanta de 1m				
Dimensiuni	Dimensiuni aparat (WxHxDmm)	140x180x350	160x240x390			
	N.W. (kgs)	5.10	7.80	8	9.1	11
	Dimensiuni ambalaj (LxWxH mm)	370x182x205	415x198x250			
	Dimensiuni bax (LxWxH mm)	435x385x385	430x415x270			

